

Notes:

[1] Certified Mill Test Reports are included for Lens Retainer [SYM#3] and Weld Pad [SYM#7]. [2] "Certificate of Conformance" stating compliance with drawing and sales order documents available upon request at time of order. [3] It is the vessel fabricator's responsibility to verify that the weld pad offers sufficient reinforcement for their particular application. [4] Read and understand Installation and maintenance manual* before installation or service. Tighten fasteners in small increments to the values shown below following torque sequence shown do not exceed a maximum 3ft/lbs difference at anytime.

MODEL#	MAX. PRESSURE	ELASTOMERS	EXPANDED PTFE	GRAPHITE
RS 2X7	150PS/FV	10 FT-LB	25~30 FT-LB	25~30 FT-LB

*Installation and maintenance manuals may be found on line at www.papailias.com or by calling the factory at +1 (201)767-4027.

						REVISION HISTORY							
					ZONE		SCRIPTIO				DATE		BY
					-	00 OR	IGINAL IS	SUE			9/12/1	14	GCP
					(5)		>						
											•		
			— 23 ¹ ⁄2" OVERALL LENGTH ———							1 2 2 2 2 2 2 8	2 6 S 2 5 L 2 4 C 2 3 L	VELD P/ SEAL GA ENS CUSHION ENS RE IEX NUT	SKET N TAINER
DIN DIN ABC	LESS OTHERWISE NOT MENSIONS ARE IN INCH MENSIONS ARE SYMME OUT CENTERLINES.	IES. FRACT TRICAL DECIM ANGLE	TING TOLERANCES: TONS: + \mathcal{V}_{64} ALS: +/-0.010 :S: + \mathcal{V}_2 deg	Rating: 1. Max.Temp glass and g				NC	OF	2 2 2 28 28 QT	2 6 S 2 5 L 2 4 C 2 3 L 3 2 H 3 1 T Y SYM D BILL OF	EAL GA ENS CUSHION ENS RE HEX NUT THREAD DESCRIF MATEF	SKET N TAINER ED STU PTION RIAL
DIM DIM ABC BRE CAS CAS AS NE	MENSIONS ARE IN INCH MENSIONS ARE SYMME OUT CENTERLINES. EAK CORNERS,REMOV STING FILLET RADII & ST CORER RADII: ½6"R SME CODE CALCULAT	ES. TRICAL E BURRS. R ONS AND ANY RES SIGHT GLASS OPE	TING TOLERANCES: TONS: + V_{64} ALS: +/- 0.010 S: + V_2 deg TRADII: V_{32} "R TRADII: V_{32} "R TRADII: V_{32} "R TRADII: V_{34} FIM SULTING ADDITIONAL MATERIA ENING TO MEET ASME CODE IS	1. Max.Temp glass and g 2. Max. Press	gasket sele	ction.	245	PEGASUS AVE,	NORTHVA	2 2 2 2 8 28 28 QT	2 6 S 2 5 L 2 4 C 2 3 L 8 2 H 8 2 H 8 1 T Y SYM D BILL OF BILL OF CONTROL OF CO	EAL GA ENS CUSHION ENS RE IEX NUT HREAD DESCRIF MATEF	SKET N TAINER ED STU PTION RIAL
DIM DIM ABC BRE CAS CAS AS NE TH	MENSIONS ARE IN INCH MENSIONS ARE SYMME OUT CENTERLINES. EAK CORNERS,REMOV STING FILLET RADII ½ ST CORER RADII: ½6"R SME CODE CALCULAT EDED TO REINFORCE IE RESPONSIBILITY O	ES. TRICAL E BURRS. R ONS AND ANY RES SIGHT GLASS OPE F THE VESSEL MAN	TING TOLERANCES: TONS: + V_{64} ALS: +/- 0.010 S: + V_2 deg TRADII: V_{32} "R TRADII: V_{32} "R TRADII: V_{32} "R TRADII: V_{34} FIM SULTING ADDITIONAL MATERIA ENING TO MEET ASME CODE IS	1. Max.Temp glass and g 2. Max. Press	gasket sele	ction.	245	PEGASUS AVE,	MC WELD	2 2 2 2 2 8 28 28 0 7 1 2 2 8 0 7 1 2 2 8 28 0 7 1 2 2 2 2 2 8 28 0 7 1 1 2 2 2 2 2 2 2 2 8 0 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 6 S 2 5 L 2 4 C 2 3 L 8 2 H 8 2 H 8 1 T Y SYM D BILL OF BILL OF CONTROL OF CO	EAL GA ENS CUSHION ENS RE IEX NUT THREAD DESCRIF MATEF MATEF	SKET TAINER ED STU PTION RIAL AS.COM
DIM DIM ABC BRE CAS CAS AS NE TH THI ANI	MENSIONS ARE IN INCH MENSIONS ARE SYMME OUT CENTERLINES. EAK CORNERS, REMOV STING FILLET RADII % ST CORER RADII: ½6"R SME CODE CALCULAT EDED TO REINFORCE IE RESPONSIBILITY O IS DRAWING IS THE SC D NEITHER THE DOCU	ES. TRICAL E BURRS. R ONS AND ANY RES SIGHT GLASS OPE F THE VESSEL MAN OLE PROPERTY OF T MENT NOR THE INFO	ING TOLERANCES: TONS: + V_{54} ALS: +/ $_{2}$ deg RADII: V_{32} "R IED FINISH: RA 125u in 7.0 WITHIN V_{4} FIM SULTING ADDITIONAL MATERIA ENING TO MEET ASME CODE IS JUFACTURER.	1. Max.Temp glass and g 2. Max. Press	gasket sele sure: 150P\$	ction. SI/FV	2451	PEGASUS AVE,	MC WELD	2 2 2 2 2 2 2 8 28 28 28 28 28 28 28 28	2 6 S 2 5 L 2 4 C 2 3 L 8 2 H 8 1 T Y SYM D BILL OF BILL OF COLJ767-4027 WW S/2X7 E LIQUID L	EAL GA ENS CUSHION ENS RE IEX NUT THREAD DESCRIF MATEF MATEF	SKET TAINER ED STU PTION RIAL AS.COM