

Notes:

[1] Certified Mill Test Reports are included for Lens Retainer [SYM#3] and Weld Pad [SYM#7].

[2] "Certificate of Conformance" stating compliance with drawing and sales order documents available upon request at time of order.

[3] It is the vessel fabricator's responsibility to verify that the weld pad offers sufficient reinforcement for the particular application.

[4] Read and Understand Installation and maintenance manual before installation or service. Tighten fasteners in small increments to the values shown below following torque sequence shown do not exceed a maximum 3ft/lbs difference at anytime.

MODEL#	MAX. PRESSURE	ELASTOMERS	EXPANDED PTFE	GRAPHITE
8"NW-FT	150PS/FV	25 FT/LB	32 FT/LB	29 FT/LB

$\sim 20131_2''$
UNLESS OTHERWISE NOTED: DIMENSIONS ARE IN INCHES. DIMENSIONS ARE SYMMETRICAL ABOUT CENTERLINES. BREAK CORNERS,REMOVE BURRS. CASTING FILLET RADII ½,"R CAST CORER RADII: ½,6"R ASME CODE CALCULATIONS AND ANY RESULTING ADDITIONAL MATERIAL NEEDED TO REINFORCE SIGHT GLASS OPENING TO MEET ASME CODE IS
THE RESPONSIBILITY OF THE VESSEL MANUFACTURER.
THIS DRAWING IS THE SOLE PROPERTY OF THE J.G. PAPAILIAS COMPANY, INC DRAWN: GCP 9/12/14 SIZE CAGE CODE DRAWING NUMBER READ AND NEITHER THE DOCUMENT NOR THE INFORMATION CONTAINED HEREIN
SHALL BE COPIED, REPRODUCED, DISCLOSED OR TRANSFERRED EXCEPT AS CHECKED: GCP 9/12/14 B 1Z740 01T128
AUTHORIZED IN WRITING BY AN OFFICER OF THE J.G. PAPAILIAS CO., INC. APPROVED: GCP 9/12/14 SCALE: 7/16 EST. WEIGHT: 70 LBS SHEET: 1 OF